Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the Specification.

Listing of Claims:

1.   (Currently amended) A mobile communication terminal comprising:

a photographic apparatus connected to the terminal;

an image processing unit for processing images produced by the photographic apparatus, wherein control information is developed responsive to movement occurring in the images; and

an operational controlling unit for corresponding an operational function of the terminal to the control information,

wherein a first image is produced from an object having a first <u>categorical feature</u> and <u>a</u> second categorical ~~features~~ <u>feature,</u> and a second image is produced from the object ~~of the first image~~, such that a first value is attributed to a first midpoint of the first categorical feature and a second value is attributed to the second categorical feature<u>,</u>

<u>wherein the image processing unit processes the images by</u>:

<u>extracting the first value from at least one of the processed images;</u>

<u>comparing the first value to an initialization value;</u>

<u>determining a first difference between the first value and the initialization value;</u>

<u>developing first control information derived from the first difference; and</u>

<u>generating a control information signal based on the first control information</u>.

2.   (Canceled)

3.   (Currently amended) The terminal of claim [[2]]<u>1</u>, wherein the initialization value is set by a user.

4.   (Canceled)

2

5.   (Canceled)

6.   (Currently amended) The terminal of claim [[5]]3, wherein [[a]]the user sets a first operational function of the terminal to correspond to the first difference.

7.   (Currently amended) A method for operating a mobile communication terminal with an integrated photographic apparatus, the method comprising:

photographing an object with the integrated photographic apparatus to produce images;

processing the images for control information;

setting an operational function of the mobile communication terminal to correspond to the control information; and

operating the mobile communication terminal based on the control information,

wherein the control information is developed responsive to movement occurring in the images,

wherein a first image is produced from an object having a first categorical feature and a second categorical features feature, and a second image is produced from the object of the first image, such that a first value is attributed to a first midpoint of the first categorical feature and a second value is attributed to the second categorical feature,

wherein processing the images comprises:

extracting the first value from at least one of the processed images;

comparing the first value to an initialization value;

determining a first difference between the first value and the initialization value;

developing first control information derived from the first difference; and

generating a control information signal based on the first control information.

8.   (Canceled)

9.   (Currently amended) The method of claim [[8]]7, further comprising:

3

extracting at least one value from at least one of the first or second images; and setting the at least one value as the initialization value.

10.	(Previously Presented) A method for operating a mobile communication terminal with an integrated photographic apparatus, the method comprising:

producing a first image from a first object with the photographic apparatus;

detecting a first diagnostic element within the first image;

deriving at least a first value from the first diagnostic element;

deriving at least a first comprehensive value from the first value;

determining a first difference between the first comprehensive value and a corresponding comprehensive initialization value derived from at least one initialization value;

assigning a first operational function of the mobile communication terminal to the first difference;

producing a second image from the first object with the photographic apparatus;

detecting a second diagnostic element within the second image;

deriving the at least one initialization value from the second diagnostic element; and

applying at least one threshold value to the comprehensive initialization value;

wherein the second diagnostic element comprises:

a preliminary diagnostic element comprising a face featured on a head of an individual; and

a secondary diagnostic element comprising a pair of eyes featured on the face of the individual;

wherein producing the second image further comprises:

attributing a first value to a first midpoint located between the eyes;

attributing a second value to a second midpoint located between a pair of shoulders;

attributing a first comprehensive value to a vector drawn through the first and second midpoint; and

4

attributing a second comprehensive value to an angle formed by the vector and a horizontal line joining the shoulders.

11-14. (Canceled)

15.   (Previously Presented) The method of claim 10, wherein the comprehensive initialization value comprises an approximate 90° angle formed by the vector and the horizontal line drawn joining the shoulders.

16.   (Previously Presented) The method of claim 10, wherein the comprehensive initialization value comprises a vector length measured when the horizontal line drawn joining eyes and containing the first midpoint is approximately parallel to the horizontal line joining the shoulders.